


# SPECIFICATION SHEET - SF5511

## CONTRACOR SILT FENCE

**ROLL LENGTH: 100'**  
**POSTS: 48" High**  
**POST SPACING: 11 stakes per roll**  
**INSTALL: As per contract**



**SF55 GEOTEXTILE: 36" Black Woven Geotextile**

PROPERTY	TEST METHOD	MARV English	MARV Metric
Tensile Strength (Grab)	ASTM D4632	65 x 65 lbs	289.3 x 289.3 N
Elongation (Grab)	ASTM D4632	15% x 15%	15% x 15%
Trapezoidal Tear Strength	ASTM D4533	35 x 35 lbs	155.75 x 155.75 N
CBR Puncture	ASTM D6241	200 lbs	890 N
UV Resistance (500 hrs)	ASTM D4355	70%	70%
Apparent Opening Size*	ASTM D4751	30 US Std. Sieve	0.60 mm
Permittivity	ASTM D4491	0.05 sec <sup>-1</sup>	0.05 sec <sup>-1</sup>
Water Flow Rate	ASTM D-4491	4 gpm/ft <sup>2</sup>	163 lpm/m <sup>2</sup>

\*Maximum Average Roll Value

The information provided is for reference purposes only and is not intended as a warranty or guarantee whether implied or inferred. This document should not be construed as engineering advice. Always consult the project engineer for project specific requirements. The property values listed above are subject to change without notice. BW Geotextiles assumes no liability in connection with the use of this information and product.

1239 Notre Dame Drive, Box 178  
Petersburg, ON N0B 2H0  
Phone: (519)778-1953 Toll Free: 1-844-778-1953  
[www.bwgeotextiles.com](http://www.bwgeotextiles.com)

02/11/2020